

Model X1

SIX-SHOOTER Concrete Reclaimer



The Model X1 SIX-SHOOTER Reclaimer is ideal for plants with lesser amounts of daily waste concrete, such as smaller ready-mix producers, smaller satellite plants, even some precast & pipe plants.

Capable of reclaiming 1/4 up to 1/2 yard-per-minute, the X1 SIX-SHOOTER is a cost-effective, affordable reclamation solution for the smaller operator.

Available in Left- or Right-Hand Sand Screw Discharge to fit your plant. Optional Sand Screw Heater package, and Automatic Start/Stop also available.

Recommended for
**Small to Mid-Size
Ready-Mix Plants**
Operating around
1 to 6 Mixer Trucks
and some **Precast & Pipe** plants.
Design capacity
1/4 to 1/2 yard³-per-minute
[up to 0.38 m³/minute]
1 Truck Discharge

Only BFK has eliminated **Grease Fittings, Shaft Seals, and Shaker Decks**, making them the **most user-friendly and affordable** Reclaimers available!

A Reclaimer so simple, you can install, operate and maintain it yourself, without the need of a factory technician!

The BFK Difference!

In line with BFK's philosophy of offering the proper size reclaimer, the X1 fits the bill for many plants with smaller amounts of waste.

Instead of using the biggest available reclaimer at smaller yards, the X1 Six-Shooter offers an alternative for producers without as much daily waste.

And the X1 offers the same design features and benefits you've come to expect from a BFK: not just another screw, paddle wheel, or bucket reclaimer!

- Less Wear & Tear
- Less Horsepower
- Less expense
- More up-time!

That's the BFK Difference!

BFK TECHNOLOGIES INC.
CONCRETE RECLAMATION SYSTEMS



Simple, Compact, Efficient
CONCRETE RECLAIMERS
Since 1997

They Simply Work!



Overall Dimensions:
10'-6" L x 6'-6" W x 6' H
[3200 x 1980 x 1800mm]
Approx. Shipping Weight:
5000# [2270kg]

X1 SIX-SHOOTER SPECIFICATIONS:

- 3HP 2.2kW Submersible Pump
- 3HP 2.2kW Rotary Screen Gearmotor
- 3HP 2.2kW Sand Screw Gearmotor

- 8" 200mm Dia. Infeed Auger
- 1/4" 6mm Square Op. Rock Screen
- 12" 305mm Dia. Sand Screw
- (1) Washout Stinger



Standard: 230/460VAC, 60Hz, 3Ø
Optional: 380/50/3Ø or 575/60/3Ø
Single Phase and other voltage/frequency combinations also available—Consult Factory.

Rights reserved to alter specifications without notice.
Metric equivalents for informational purposes only.



Ships Worldwide in (1) 20' Standard Container



WARNING: Cancer and Reproductive Harm—
www.P65Warnings.ca.gov

ONE Screen
ONE Screw
ONE Pump
...only 9 Horsepower

BFK Technologies Inc.
1113 Park Avenue
Kiel WI 53042 USA

Tel: 920.894.1113
Fax: 920.894.4991
Email: sales@bfktech.com

www.BFKTECH.com
1.888.BFK.8BFK
1.888.235.8235

