

Model X2

SIX-SHOOTER Concrete Reclaimer



The Model X2 Double-Wide SIX-SHOOTER Reclaimer is ideal for plants with lesser amounts of daily waste concrete, but still need the ability to wash-out 2 mixer trucks at once.

The Model X2 SIX-SHOOTER is capable of reclaiming from 1/4 to 1/2 yard-per-minute, making it as fast as many competitors largest machines!

Make sure to compare thru-put and No. of Truck capabilities when comparing to competitive brands!

Available in Left- or Right—Hand Sand Screw Discharge to fit your plant. Optional Sand Screw Heater package, and Automatic Start/Stop also available.

Generally recommended for
**Small to Mid-Size
Ready-Mix Plants**

Operating around
3 to 10 Mixer Trucks

Design capacity
1/4 to 1/2 yard³-per-minute
[up to 0.38 m³/minute]

2 Truck Discharge.

Only BFK has eliminated **Grease Fittings, Shaft Seals, and Shaker Decks**, making them the most user-friendly and affordable Reclaimers available!

A Reclaimer so simple, you can install, operate and maintain it yourself, without the need of a factory technician!

The BFK Difference!

The X2 is a versatile system, fitting the bill for the smaller producers, while increasing traffic flow at the reclaimer.

A “Double-Wide” version of the Model X1, the X2 allows 2 trucks to simultaneously wash out.

And the X2 offers the same design features and benefits you’ve come to expect from a BFK: not just another screw, paddle wheel, or bucket reclaimer!

- Less Wear & Tear
 - Less Horsepower
 - Less expense
 - More up-time!
- That’s the BFK Difference!

BFK TECHNOLOGIES INC.
CONCRETE RECLAMATION SYSTEMS



**Simple, Compact, Efficient
CONCRETE RECLAIMERS**

Since 1997

X2 SIX-SHOOTER SPECIFICATIONS:

- 5HP 3.7kW Submersible Pump
- 3HP 2.2kW Rotary Screen Gearmotor
- 3HP 2.2kW Sand Screw Gearmotor
- 8" 200mm Dia. Infeed Auger
- 1/4" 6mm Square Op. Rock Screen
- 12" 305mm Dia. Sand Screw
- (2) Washout Stingers

Overall Dimensions:
10'-6" L x 6' H x 8' W
[3200 x 1800 x 2400mm]

Approx. Shipping Weight:
5400# [2450kg]

Standard: 230/460VAC, 60Hz, 3ø
Optional: 380/50/3ø or 575/60/3ø
Single Phase and other voltage/frequency combinations also available—Consult Factory.

Rights reserved to alter specifications without notice.
Metric equivalents for informational purposes only.

Ships Worldwide in (1) 20' Standard Container

ONE Screen

ONE Screw

ONE Pump

**...only 11
Horsepower**

**They
Simply
Work!**



WARNING: Cancer and
Reproductive Harm—
www.P65Warnings.ca.gov

BFK Technologies Inc.
1113 Park Avenue
Kiel WI 53042 USA

Tel: 920.894.1113
Fax: 920.894.4991
Email: sales@bfktech.com

www.BFKTECH.com
1.888.BFK.8BFK
1.888.235.8235

